

Monday, November 14, 2016

To Whom it may concern
ADIT Ltd
Moshav Bne Reem
79840 Israel

To Whom it may concern.

Ref:- Chemfix Products Ltd (UK) as the manufacturer of ADIT Chemical Anchors

This letter confirms the relationship between Chemfix Products Ltd, as a manufacturer of own label chemical anchoring products in cartridges, wholly produced in the Dewsbury factory and exported worldwide.

ADIT Ltd, 79840 Israel is the customer of Chemfix and is supplied with labelled product under the ADIT "Chemical Pro" branding. Each ADIT product pertains to the Chemfix range as follows:

"Adit AC500Pro" is the same resin and cartridge as "Chemfix Pure Epoxy"

"Adit Chemfix500Pro" is the same resin and cartridge as "Chemfix 500"

"AC100Pro" is the same resin and cartridge as "Chemfix CH+"

"CT50Pro" is the same resin and cartridge as "Chemfix PESF"

Yours sincerely



Urs Joos
Commercial & Marketing Director
Chemfix Products Limited

Confirmation

LEED v4 and v4.1

On 6 May 2021, Eurofins Product Testing A/S received a sample of sealant with the product name:

Chemfix PESF (PESF TOP)

supplied by

Chemfix Products Ltd

The sample was supplied as being representative of the manufactured product, and it has been tested in accordance with the relevant ISO 16000, EN 16516 and ASTM D2369 testing standards (See test report no. 392-2021-00231001_A_EN and no. 392-2021-00231002_XG_EN).

The test results of the tested sample indicate that the product qualifies for LEED v4 and LEED v4.1 BETA (February 2021) projects outside the US by showing compliance with the specifications for VOC emissions and VOC content by complying with:

VOC emissions specifications in LEED EQ credit "Low-Emitting Materials" for LEED projects outside the US:

- The requirements of LEED v4.1 BETA (February 2021) by not exceeding the LCI values mentioned in the German AgBB Testing and Evaluation Scheme (2018), showing an overall R-value below or equal to 1 and having a TVOC according to EN 16516 below or equal to 1,000 µg/m³, a sum of VOC without LCI less than 100 µg/m³ and a formaldehyde emission below or equal to 10 µg/m³; all after 28 days.
- The requirements of LEED v4 by complying with:
 - The requirements of Indoor Air Comfort Gold version 7.0 (May 2020).

VOC content specifications in LEED EQ credit "Low-Emitting Materials" for LEED projects globally:

- The requirements of LEED v4 and LEED v4.1 BETA (February 2021): South Coast Air Quality Management District (SCAQMD) Rule 1168 (2017) for other adhesive having a VOC content below 250 g/L

19 July 2021



Rasmus Verdier
Analytical Service Manager



Pernille Krintel
Analytical Service Manager

Confirmation

LEED v4 and v4.1

LEED® is the preeminent program for the design, construction, maintenance and operations of high-performance green buildings. USGBC® and the related logo are trademarks owned by the U.S. Green Building Council and are used with permission.